

December/2018 Exam Pass 100% !Braindump2go 300-360 VCE and 300-360 PDF 185Q Instant Download[Q129-Q139]

December/2018 Braindump2go 300-360 Exam Dumps with PDF and VCE New Updated Today! Following are some new 300-360 Real Exam Questions:1.|2018 Latest 300-360 Exam Dumps (PDF & VCE) 185Q

Download:<https://www.braindump2go.com/300-360.html>2.|2018 Latest 300-360 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNaFhjTjl4Uk0tbDg?usp=sharing>QUESTION 129A company has deployed a centralized wireless architecture at their headquarters. In this type of deployment, to which network layer do you recommend that the WLC connect?A. distribution layerB. Data center layerC. session layerD. access layer**Answer: A**

QUESTION 130Which three parameters are used by Cisco Prime Infrastructure to generate heat maps? (Choose three.)A. the RSSI prediction modelB. the AP SNRC. the bandwidth utilizationD. the AP transmit powerE. the antenna orientationF. the number of associated clients**Answer: ADE**Explanation:An RF heatmap is a graphical representation of RF wireless data where the values taken by variables are represented in maps as colors. The current heatmap is computed based on the RSSI prediction model, Antenna Orientation, and AP transmit power.

https://www.cisco.com/c/en/us/td/docs/net_mgmt/prime/infrastructure/3-0/user/guide/pi_ug/wireless-map_s.htmlQUESTION

131An engineer has performed a post-deployment site survey and noticed that access points were installed in suboptimal locations due to physical restrictions and obstacles. Which action must the engineer take to resolve this deployment issue?A. Set DCA Channel Assignment Method to freeze.B. Set all Auto RE parameters to factory defaultC. Set TPC maximum and minimum power levels.D. Set static channels on all AP radios.**Answer: C**Explanation:Suspect poor coverage/not enough AP density -- If AP transmit power is already at the maximum, you can enable the lower data rates to allow clients to connect from farther away. This has a negative impact on performance, but it can help the customer understand that additional APs might be necessary.

<https://www.cisco.com/c/en/us/support/docs/wireless/5500-series-wireless-controllers/116057-site-survey-guidelines-wlan-00.html>QUESTION

132An engineer is deploying outdoor Cisco Aironet 1500 Series Access Points and wants to protect the network from overvoltage transients.Which two protection methods must be used? (Choose two)A. lightning arrestorB. grounding lugC. antenna diversityD. temperature controlE. PoE output**Answer: AB**Explanation:

https://www.cisco.com/c/en/us/td/docs/wireless/access_point/1550/installation/guide/1550hig/1550_ch2.htmlQUESTION

133A wireless engineer is configuring VoWLAN on a WLC.Which configuration should be implemented on the router or switch that is connected to the WLC?A. The interface on the switch or router should trust the CoS settings of the WLC.B. The interface on the WLC should mark all packets as EF.C. The interface on the switch or router should strip all CoS markings on the IEEE 802.11 header.D. The interface must be configured as a Layer 3 interface.**Answer: A**Explanation:We recommend that the QoS policy on the router/switch interfaces connected to the WLC be set to trust the CoS settings of the WLC. This means that the wired network responds to the CoS values controlled by the QoS policy set on the WLC. The WLC does not enforce any policy that changes the WLAN client DSCP values. The WLC policy effects will only be seen in the CoS values associated with the WLAN client traffic. If the routers and switches connecting to the WLC are set to trust DSCP, then a DSCP policy must be created and maintained on those router and switch interfaces--in addition to the policies applied on the WLC. For more information on WLAN QoS and traffic classification, refer to the Chapter 3, "Voice over WLAN Radio Frequency Design."

https://www.cisco.com/c/en/us/td/docs/solutions/Enterprise/Mobility/vowlan/41dg/vowlan41dg-book/vowlan_ch8.html

QUESTION 134A customer is preparing to deploy a wireless network in a stadium and is identifying coverage area requirement for the patrons in suite areas.Which two attributes are relevant to determining these coverage requirements? (Choose two.)A. hours of operationB. encryption typeC. authentication typeD. number of usersE. device types**Answer: CE**QUESTION

135Which purpose of using Metageek Chanalyzer during site survey is true?A. to verify the antenna pattern of the APsB. to show only the usage of the 2.4 GHz spectrumC. to determine the sources of non-802.11 interferencesD. to verify the different channels used during the design of Wi-Fi networks**Answer: C**Explanation:A spectrum analysis tool like Chanalyzer + Wi-Spy which shows you non-WiFi interference from devices like cordless phones, wireless video cameras, and microwave ovens. After you've detected an otherwise-invisible non-WiFi device, Chanalyzer + Wi-Spy can identify it and track it down.

<https://support.metageek.com/hc/en-us/articles/205050684-Is-Chanalyzer-a-Site-Survey-Tool>QUESTION 136When should a Layer I site survey be performed?A. briefly during the predictive site surveyB. briefly during the passive site surveyC. for an extended period of time during the predeployment site survey and during the post-deployment site surveyD. for an extended period of time during the predeployment site survey only**Answer: C**QUESTION 137After installation of a new data-only wireless network, an engineer found that RRM has set all of the APs to a power level of 1.Which option describes the reason for this?A. APs are too

far apart for the set data rates.B. EORRM is enabledC. High co-channel interference exists.D. DTTPC value is set too high.

Answer: AQUESTION 138An engineer has performed a post-installation site survey using Ekahau Site Survey with a recommended adapter.Which two metrics can be different between the adapter used to survey and the client adapter? (Choose two.)A. SNR B. data rate C. DFS D. channel overlap
Answer: AB
Explanation:You must take note on what adapter was used in a site survey. The adapter should have similar characteristics to the adapters on the devices that are actually to be used in the wireless network. You should always verify what type of client adapter was used throughout the survey. A client adapter with a better receiver sensitivity and stronger antenna does not provide accurate results to compare against clients that are actually used in production.
QUESTION 139A wireless phone user is having roaming difficulties and is experiencing gaps in the conversation while roaming. WLC WLAN is configured as IEEE 802.1X and WPA2 and Aironet information element.What should be configured to fix the problem?
A. IEEE 802.1X with Cisco Centralized Key Management
B. IEEE 802.1X EAP-FAST
C. DHCP required and DHCP proxy on WLC
D. WPA1 and PSK
Answer: A
Explanation:

https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-1/Enterprise-Mobility-8-1-Design-Guide/Enterprise_Mobility_8-1_Deployment_Guide.pdf!!!RECOMMEND!!!1.|2018 Latest 300-360 Exam Dumps (PDF & VCE) 185Q

Download:<https://www.braindump2go.com/300-360.html>2.|2018 Latest 300-360 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=1MSGk2z6Rd8](https://www.youtube.com/watch?v=1MSGk2z6Rd8)